



NOTE:
 AT SYSTEM LOAD OF 0LBS, DISTANCE = 2.47IN
 AT SYSTEM LOAD OF 50LBS, DISTANCE = 2.80IN
 AT SYSTEM LOAD OF 100LBS, DISTANCE = 2.90IN

DISTANCE: TOP OF FIRST COLLAR TO BOTTOM OF SECOND COLLAR
SYSTEM LOAD: TOTAL LOAD BELOW SECOND COLLAR

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF MILESTONE AV TECHNOLOGIES NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF MILESTONE AV TECHNOLOGIES.

CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE.			CHIEF 6436 CITY WEST PKWY EDEN PRAIRIE MN, 55344 PHONE: 866-977-3901 FAX: 877-894-6918
DRAWN BY	CT	5/29/2018	
ENG APPROVAL			DESCRIPTION XL VIBRATION ISOLATOR COUPLER
MFG APPROVAL			MODEL NO. CMA348
QA APPROVAL			SIZE DWG. NO. B TECH-000932
SHEET 1 OF 1			SCALE 1:8
			REV. 00