FOR YOUR IMAGE

DA-LIT



Superior Screen Performance - No Wall Needed

Imagine that you could add a screen anywhere you need it without worrying about glare issues, no matter how much light is in the room. Together, Da-Lite and Chief make this possible.

When you combine a Parallax Thin ambient light-rejecting screen from Da-Lite and a Fusion ceiling mount from Chief, you get superior screen performance that can be mounted anywhere – no wall needed.

The Parallax Difference

With the Parallax surface, no matter how much uncontrolled ambient light is in the room, the result is always a vivid, high-contrast image.

Each layer of Parallax plays a role in preserving the image that is reflected back to the viewer. Some layers absorb light while one layer shaped like a microscopic saw-tooth blocks light from above. And while other ambient light rejecting surfaces cannot be used with laser projectors, Parallax is 4K-ready and compatible with laser projection.

A Perfect Pair

The Parallax Thin quickly and easily attaches to a Chief Fusion ceiling mount right out of the box. No additional equipment needed! And with a Fusion ceiling mount, achieving the perfect positioning is made easy with installer-friendly features.

The solution is a great fit for

•

- Digital signage
- Restaurants .
- Houses of worship
- Corporate entryways

Parallax 0.8

Gain: 0.8 | Horizontal Viewing Half Angle: 85°

For standard throw projectors (15:1 throw or greater)

- 17° vertical half angle •
- Less than 2% color shift
- Available in sizes up to 120" diagonal
- Laser projection compatible

Choose from Parallax 0.8,

Ships fully assembled

Weight range 50-95lbs depending on size

Thin 3/8" bezel aluminum frame

UST 0.45 or 2.3

Parallax UTS 0.45

Anywhere you need a glare-free screen and mounting

Gain: 0.45 | Horizontal Viewing Half Angle: 80°

For ultra-short-throw projectors (0.4:1 throw or less)

- 55° vertical half angle •
- Less than 2% color shift
- Available in sizes up to 120" diagonal
- Laser projection compatible

What You Need



XCM1U Fusion[™] XL Single Pole **Ceiling Mount**

- + 5°/- 20° tilt •
- 250 lbs (113.4 kg) weight • capacity
- UL Listed and TAA Compliant



95% ALR

XCM7000 Fusion[™] XL Dual Pole **Ceiling Mount**

- + 7.5°/- 20° tilt
- 300 lbs (136.1 kg) weight capacity
- UL Listed and TAA Compliant



Parallax Thin

1" depth

.

.

FOR YOUR IMAGE | milestone.com

USA	P 866.977.3901	E info@da-lite.com
CANADA	P 877.345.4329	E canadainfo@milestone.com
EMEA	P +31 495 580 840	E emea.sales@milestone.com
APAC	P +852 2145 4099	E asia.da-lite@milestone.com

In British Columbia, Milestone AV Technologies ULC carries on business as MAVT Milestone AV Technologies ULC. ©2018 Milestone AV Technologies, 170327 1/18 Da-Lite is a registered trademark of Milestone AV Technologies,

All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.



- 96% ALR

to a wall isn't an option!