Motorized projection screen for wall or ceiling installations







Product specifications:


- Electrically operated projection screen 230 volt (50Hz) with a usage of no more than 0.69 Ampere (158.7 Watt).
- The motor is mounted on the left side an can be reached through a service hatch in the steel casing.
- The motor is mounted inside the roller, 65 cm long, 4 wire, 12 rotations per minute, maintenance free, integrated brake and thermal overload cut-out.
- The end positions are pre-set.
- The 4 wire connection is integrated into the end cap and can be connected to the electric installation with the connector and standard cable.
- Suitable for wall and ceiling mounting with the supplied flexible mounting brackets which can be positioned 100cm from either endcap.
- The steel square casing (23,9x27,6cm) is galvanised on the inside and on the outside powder coated with a matte structure coating (RAL 9010).
- The screen fabrics are flame retardant and seamless in the viewing area.
- Each side of the surface to have tab guide cable system to maintain even lateral tension and hold surface flat.
- Custom slat bar with added weight maintains vertical tension on the screen surface. The ends of the slat to be protected by heavy duty plastic caps enclosing a preset adjustable mechanism for screen tensioning.
- The projection fabrics have a black backing.
- Standard 3 position wall switch is supplied.
- The projection screen is CE marked and satisfies the strictest quality and safety requirements.

Aspect Ratios:

16:10

16:9

4:3




Available dimensions

Minimum width: Maximum width:

400 cm 450 cm





<u> </u>		Viewing Area	Dimensions			Black drop	Net weight	
		cm	L1 mm	L2 mm	L3 mm	cm	kg	
16:10	254 x 400	244 x 390	4430	3330	4196	30	133	
	285 x 450	275 x 440	4970	3870	4620	30	144	
16:9	229 x 400	219 x 390	4430	3330	4158	30	132	
	258 x 450	248 x 440	4970	3870	4608	30	143	
4:3	300 x 400	290 x 390	4430	3330	4246	30	135	
	340 x 450	330 x 440	4970	3870	4646	30	146	

Accessories - control options

For projection screens with a standard motor / delivered as standard with a wall switch

- All-in-One Control Box, which contains:
 - > Relay (dry contact)
 - > RF control, including remote control
 - > IR control, including remote control
 - > Manual switch
 - > 12v DC trigger
- Power Sensing Trigger (need All-in-One Box to function)
- Easy Install plug & play relaybox with potential free contacts
 - > Easy Install plug & play RS232/RS422 control kit
 - > Easy Install plug & play RS232/RS422 with IP control kit
- Keyswitch

For projection screens with an RF motor / delivered as standard with a remote control

- RF wall-mounted transmitter (433,92 Mhz)
- 4-channel RF remote control (433,92 Mhz)

Accessories - installation

- Ceiling brackets (100 cm.)
- Set extension brackets
- Bracket kit for easy mounting in soffit



Available standard resolution projection surfaces

All screen surfaces are seamless in the viewing area.

Matte White

Gain: 1.0 Viewing Angle: 120° Base material: Vinyl Fire retardancy: B2 Black backing: Yes Opacity rating: > 99 %

Seamless: Yes

GreenGuard certification:




Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Certification number

Greenguard -5100-410

Greenguard Gold -5100-420



Yes

Pearlescent

Gain: 1.5 Viewing Angle: 80° Base material: Vinyl Fire retardancy: B2 Black backing: Yes Opacity rating: > 99 % Yes

Seamless:


GreenGuard certification:

Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Certification number

Greenquard -

Greenguard Gold



Yes

Da-Tex (rear projection)

Gain: 1.3 Viewing Angle: 60° Base material: Vinyl Fire retardancy: B2 Seamless: Yes

GreenGuard certification:



Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building 1.4 Materials, Finishes and Furnishings 1.2

Certification number

Greenquard -

Greenguard Gold -5106-420



Certifications

- Products are manufactured in an ISO14001 certified facility
- Projecta is an ISO 9001 certified company
- REACH Registration, Evaluation, Authorisation and Restriction of Chemical substances.
- RoHS Restriction of Hazardous Substances.
- WEEE Waste Electronic and Electrical Equipment Regulations.



Customisation

Give exact the sizes	of the projection screen	n you need:				
Viewing size:	Heigth (cm.) x	width (cm.)				
Surface:		Border top:	(cm.)	Border bottom:	(cm.	
RAL color case and	plastic parts: RAL					
Motor posit	tioned on right side		Screen fabric mounted reversely			
Remarks:						



Available High Resolution projection surfaces

All screen surfaces are seamless in the viewing area.

HD Progressive 0.6

Gain: 0.6 Viewing Angle: 170° Base material: Vinyl Fire retardancy: B2 Black backing: Yes

Opacity rating: > 99 % Yes Seamless:

GreenGuard certification:




Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Certification number

Greenguard -11065-410

Greenguard Gold -11065-420





HD Progressive 0.9

Gain: 0.9 Viewing Angle: 170° Base material: Vinyl Fire retardancy: B2 Black backing: Yes > 99 % Opacity rating:

Seamless: Yes

GreenGuard certification:

Yes


Yes

Standard: UL 2818 - 2013 Standard Materials, Finishes and Furnishings

Certification number

Greenguard -11066-410

Greenquard Gold -11066-420



HD Progressive 1.1

Gain: 1.1 170° Viewing Angle: Base material: Vinyl Fire retardancy: B₂ Black backing: Yes > 99 % Opacity rating:

Seamless: Yes


GreenGuard certification:

Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Certification number

Greenguard -

Greenguard Gold -



HD Progressive 1.3 Gain: 1.3 Viewing Angle: 150° Base material: Vinyl Fire retardancy: B2 Black backing: Yes Opacity rating: > 99 % Seamless: Yes GreenGuard certification:


Yes

Standard: UL 2818 - 2013 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Certification number

Greenguard -42729-410


Greenquard Gold -42729-420







Elpro Large - wall mounting bracket included

(Dimensions in mm)








front view


side view

Elpro Large - ceiling mounting bracket included

(Dimensions in mm)









Warranty

Da-Lite provides a limited 5 year warranty on the Elpro Concept range and a limited 2 year warranty on all other products. The warranty on the motor of electrical screens is 5 year. All warranties are in effect beginning the date the product was invoiced by Projecta.