


# Ultra Wide Angle

Tensioned Projection Surface - high resolution



**Standard:**  
UL 2818 - 2013 Standard for Chemical  
Emissions for Building Materials,  
Finishes and Furnishings

**Certification number:**  
Greenguard Gold - 5117-420

## REAR PROJECTION

### Feature:

Exceptionally wide viewing angle

### Application:


For rear projection installations with high resolution projectors and edge blending

Ultra Wide Angle is a flexible vinyl rear projection surface designed for wide viewing angles with controlled ambient light. It is ideal for installations using multiple projection edge blending or wide format screens with short focal length projection lenses. Ultra Wide Angle dramatically reduces the potential of hot spotting. Seamless in any width up to 488 cm in height.

## Screen fabric specifications:

Gain	0.65	Ambient light resistance	controlled lighting recommended
Viewing Angle	156°	Coating	rear
Application	rear projection	Coating type	color neutral
Base material	vinyl	Thickness	~0.30 mm
Fire retardancy	B2 DIN4102-1 M2 NFP 92-503	Weight	~400 g/m <sup>2</sup>
Black backing:	no	Ability to seam	good
Edge Blending properties	excellent	Tear strength	good
Size limitations	488 cm high x any width	Foldable	yes
Seamless	up to a height of 488 cm	Cleanable	yes
GreenGuard Certification	Yes	Screen type	DIN 19045-4 - R (rear)

### Gain



**PROJECTA**

A BRAND OF MILESTONE AV TECHNOLOGIES BV

REFLECTING YOUR VISION P.: +31 (0) 495 580 840 | F.: +31 (0) 495 580 845 | [emea.sales@milestone.com](mailto:emea.sales@milestone.com) | [www.milestone.com](http://www.milestone.com)