



ASSEMBLY INSTRUCTIONS FOR
HOLO Screen



Suggested Methods of Installation

Screen Assembly

1. Locate the two Griplock Gliders attached to the top of the screen frame.
2. Unscrew the safety cap on each Glider, but do not remove. Throughout installation, be sure that the safety cap remains attached.
3. Into the top of each Glider, thread the straight end of one galvanized stainless steel cable (included). Ensure the cable passes at least 1" beyond the body of the Glider.
4. Pull the cables through the Gliders until the remaining length (the loop end) is at an appropriate distance (depending on circumstances of setup). Ensure both cables are of approximately equal distance between the Glider and the loop.
5. Raise the screen to hook each loop around customer supplied support or structure.
6. Ensure the screen is level by adjusting the length of each cable through the Gliders.
7. Once screen is in position, tighten the safety cap at the top of each Glider to secure.



Specifications For The Griplock Glider System

When threading the cable through the Glider, always allow it to pass at least 1" beyond the body of the Glider. Avoid angled pulls of the cable in excess of 5° off axis to the Glider. When cutting off excess cable, always leave at least 1" of cable showing. Cables will generally not fray when cut, but just in case apply a drop of superglue. The Griplock System is not recommended for outdoor use: it should not be exposed to water or wind, or be allowed to oscillate continuously. Avoid placing fixtures close to HVAC vents or in chemical-laden environments, such as indoor swimming pools. To release, unscrew the safety cap and depress to withdraw the cable.

For more information, please visit www.griplocksystems.com.



A Milestone AV Technologies Brand

3100 North Detroit Street
Warsaw, Indiana 46582
P: 574.267.8101 or 800.622.3737
F: 574.267.7804 or 877.325.4832
E: info@da-lite.com
www.da-lite.com

DL-0396 6.14

© 2014 Milestone AV Technologies LLC. Printed in U.S.A.